

EJOFAST® self-drilling screw JF3-plus-6.8

EJOFAST



Application range

- > Fastening profiled steel and aluminium sheet and sandwich panels to timber substructure


Characteristics

- > A2 stainless steel with hardened steel drill point
- > Stainless steel sealing washer
- > Pre-assembled sealing washer
- > Reduced swarf fastening
- > Assembly without pre-drilling
- > Non-skid application
- > High load-carrying capacity


Cross references

ORKAN storm washers
 Socket wrench insert SW8
 Cordless screwdriver ASCS 6.3
 Long screw support SH2

Applications



Technical specifications



Certifications



Product online



Order description	Length [mm]	Thread length [mm]	Height component I [mm]	PU [pieces]	Price/100 [EUR]	Article number	EAN
Sealing washer E16, Ø 16 mm							
JF3-Plus-6.8X 40 E16	40	40	-	250		3594067393	4061245080611
JF3-Plus-6.8X 40 E16 VE100	40	40	-	100		6594067393	4061245081304
JF3-Plus-6.8x60 E16	60	60	0-10	250		3594167393	4061245080635
JF3-Plus-6.8x60 E16 VE100	60	60	0-10	100		6594167393	4061245081335
JF3-Plus-6.8x80 E16	80	75	0-30	250		3594267393	4061245081366
JF3-Plus-6.8x80 E16 VE100	80	75	0-30	100		6594267393	4061245081373
JF3-Plus-6.8x100 E16	100	75	20-50	100		3594367393	4061245081403
JF3-Plus-6.8x120 E16	120	75	40-70	100		3594467393	4061245081434
JF3-Plus-6.8x140 E16	140	75	60-90	100		3594567393	4061245081465
JF3-Plus-6.8x160 E16	160	75	80-110	100		3594667393	4061245081496
JF3-Plus-6.8x180 E16	180	75	100-130	100		3594767393	4061245081526
JF3-Plus-6.8x200 E16	200	75	120-150	100		3594867393	4061245081557
JF3-Plus-6.8x220 E16	220	75	140-170	100		3594967393	4061245081601
JF3-Plus-6.8x240 E16	240	75	160-190	100		3595067393	4061245081632
JF3-Plus-6.8x260 E16	260	75	180-210	100		3595167393	4061245081663
JF3-Plus-6.8x280 E16	280	75	200-230	100		3595267393	4061245081694
JF3-Plus-6.8x300 E16	300	75	220-250	100		3595367393	4061245081724

Order description	Length [mm]	Thread length [mm]	Height component I [mm]	PU [pieces]	Price/100 [EUR]	Article number	EAN
Sealing washer E19, Ø 19 mm							
JF3-Plus-6.8X 40 E19	40	40	-	250		3594066393	4061245081311
JF3-Plus-6.8x60 E19	60	60	0–10	250		3594166393	4061245081342
JF3-Plus-6.8x80 E19	80	75	0–30	100		3594266393	4061245081380
JF3-Plus-6.8x100 E19	100	75	20–50	100		3594366393	4061245081410
JF3-Plus-6.8x120 E19	120	75	40–70	100		3594466393	4061245081441
JF3-Plus-6.8x140 E19	140	75	60–90	100		3594566393	4061245081472
JF3-Plus-6.8x160 E19	160	75	80–110	100		3594666393	4061245081502
JF3-Plus-6.8x180 E19	180	75	100–130	100		3594766393	4061245081533
JF3-Plus-6.8x200 E19	200	75	120–150	100		3594866393	4061245081564
JF3-Plus-6.8x220 E19	220	75	140–170	100		3594966393	4061245081618
JF3-Plus-6.8x240 E19	240	75	160–190	100		3595066393	4061245081649
JF3-Plus-6.8x260 E19	260	75	180–210	100		3595166393	4061245081670
JF3-Plus-6.8x280 E19	280	75	200–230	100		3595266393	4061245081700
JF3-Plus-6.8x300 E19	300	75	220–250	100		3595366393	4061245081731
Sealing washer E22, Ø 22 mm							
JF3-Plus-6.8X 40 E22	40	40	-	250		3594013393	4061245081328
JF3-Plus-6.8x60 E22	60	60	0–10	250		3594113393	4061245081359
JF3-Plus-6.8x80 E22	80	75	0–30	100		3594213393	4061245081397
JF3-Plus-6.8x100 E22	100	75	20–50	100		3594313393	4061245081427
JF3-Plus-6.8x120 E22	120	75	40–70	100		3594413393	4061245081458
JF3-Plus-6.8x140 E22	140	75	60–90	100		3594513393	4061245081489
JF3-Plus-6.8x160 E22	160	75	80–110	100		3594613393	4061245081519
JF3-Plus-6.8x180 E22	180	75	100–130	100		3594713393	4061245081540
JF3-Plus-6.8x200 E22	200	75	120–150	100		3594813393	4061245081571
JF3-Plus-6.8x220 E22	220	75	140–170	100		3594913393	4061245081625
JF3-Plus-6.8x240 E22	240	75	160–190	100		3595013393	4061245081656
JF3-Plus-6.8x260 E22	260	75	180–210	100		3595113393	4061245081687
JF3-Plus-6.8x280 E22	280	75	200–230	100		3595213393	4061245081717
JF3-Plus-6.8x300 E22	300	75	220–250	100		3595313393	4061245081748
*Calculated with the setting depth of 50 mm recommended by EJOT. Deviating setting depths possible according to ETA.							