

## EJOFAST® self-drilling screw JF2-2H-4.8



### Cross references

Socket wrench insert  
Cordless screwdriver ASCS 6.3

### Application range


- > Side lap stitching of profiled steel sheet

### Properties


- > Case-hardened steel, zinc-plated
- > Fastening without swarf\*
- > With free spin zone under screw head for side lap stitching
- > Non-skid application
- > Suitable for installation with the EJOFAST® JF screwdriver

\***Without swarf** means that - contrary to conventional self-drilling screws with classic cutting bit - ribbon swarfs, spiral swarfs or spiral swarf pieces are avoided.


### Applications



### Technical data



### Certifications



EJOFAST® JF screwdriver  
available as rental equipment.

### Online shop



Order description	Length [mm]	Diameter [mm]	Clamp thickness [mm]	PU [pieces]	Price/100 [EUR]	Article number	EAN
<b>loose</b>							
JF2-2H-4.8x19	19	4.8	0 - 9	1,000		7 280 628 601	4061245014524
JF2-2H-4.8x19 VE100	19	4.8	0 - 9	100		6 280 628 601	4061245014890
<b>collated</b>							
JF2-2H-4.8x19 collated	19	4.8	0 - 9	500		3 375 000 000	4061245016573