

Self-drilling screw JT4-LT-Xt-3H/6-5.5x25



Cross references

XT centring grommet F
 XT centring grommet S
 LT-XT Tool TX25

Application range

- > For fastening plain aluminium composite panels to 2 mm aluminium substructures
- > Only to be used in combination with XT fixed and sliding point grommets

Properties

- > A2 stainless steel
- > Pan head

Advantages

- > To cover slotted holes and large pre-drill diameters
- > Also available as painted version
- > Flat screw head for aesthetic facade design
- > Easy assembly and reliable sliding thanks to optimised free spin zone
- > Regulated by the building authorities in test certificate P-S 18 0447
- > Easy removal of protective film
- > Centering grommet collar protects the facade cladding surface from scratches
- > No rivet installation gauge or drilling gauge necessary
- > Non-threaded part under the screw head allows an intentional further rotation of the screw head after connecting surface


Notice

Please note the respective approval for the exterior wall cladding and the assembly instructions of the manufacturer.


Applications



Technical specifications



Certifications



Installation process



Product online



Order description	Length [mm]	max. panel thickness [mm]	PU [pieces]	Price/100 [EUR]	Article number	EAN
JT4-LT-Xt-3H/6-5.5x25 KD16	25	4.0	500		7384216300	4061245073132