

Window screw type Super-E



Cross references

Bit cross recess H2

Application range

- > Fastening of tilt and turn fittings in PVC profiles and in steel or GRP inserts
- > Fixing locking plates, strips and bearings

Properties



- > Cost-effective screw for fittings with one-start thread
- > Under-head serrations for increased safety against stripping
- > Slightly curved head for flawless appearance even with bevelled installation
- > Roll-sorted quality for automated fastening
- > Case-hardened steel
- > EJOSEAL is an inorganic, transparent sealant, to significantly increase the corrosion and heat resistance of fastening elements with zinc or zinc alloy coatings. EJOSEAL does not contain wax and is ideally suitable for direct fastening into plastic.

Processing information

- > Can also be fastened in steel, pre-drilling required (see chart)
- > Can also be fastened in GRP, pre-drilling might be required

Sheet thickness	Pre-drilling diameter
1.5 mm	3.0 mm
2.0 mm	3.0 mm
2.5 mm	3.0 mm

Technical specifications



Product online



Order description	Length [mm]	PU [pieces]	Price/100 [EUR]	Article number	EAN
EJOSEAL					
Window screw Super-E 4.2x16	16	1000		2253416607	4061245041438
Window screw Super-E 4.2x20	20	1000		2253420607	4061245041421
Window screw Super-E 4.2x22	22	1000		2253422607	4061245041414
Window screw Super-E 4.2x25	25	1000		2253425607	4061245041407
Window screw Super-E 4.2x28	28	1000		2253428607	4061245041391
Window screw Super-E 4.2x30	30	1000		2253430607	4061245041384
Window screw Super-E 4.2x35	35	1000		2253435607	4061245041377
Window screw Super-E 4.2x40	40	1000		2253440607	4061245041360
Window screw Super-E 4.2x45	45	1000		2253445607	4061245041353
Window screw Super-E 4.2x55	55	1000		2253455607	4061245041346