

VSD 2G 8U Cavity Wall Repair Anchor



Application range

- > For subsequent securing of outer sheets to buildings
- > Cost-effective restoring of the structural integrity

Properties


- > Additional length 145 mm for subsequent securing of face bricks
- > Optimised expansion zone - now also for post-securing of vertically perforated clinkers
- > Universal expansion zone - secure installation in all substrates (A-C)
- > Double expansion wall anchor: simultaneous embedment in both the supporting wall and the outer sheet
- > The use of A4 stainless steel screws guarantees corrosion protection
- > With general building authorities approval
- > Clean and fast installation
- > Can be installed at 0°C

Notice


The VSD cavity wall repair anchor enables the subsequent renovation of double-sheet masonry. Advanced corrosion or a complete lack of wire anchors can lead to decreased stability of the curtain wall and possibly cause considerable physical injury. In particular curtain walls made before 1979 should be subject to further inspection. When renovating the outer facade, the stability of the curtain wall must be verified. The EJOT® VSD is a particularly cost-effective solution for subsequent installation between load-bearing shell and curtain wall.

Cross references

- Cordless screwdriver ASCM QSW
- Cordless hammer drill ABH
- Hammer drill SDS plus
- Bit hexalobular TX30
- Tool belt
- Cleaning brush
- Blow-out pump



Technical specifications



Certifications



Base materials

- Suitable for load-bearing inner sheets made of
- > Concrete
 - > Solid brick
 - > Perforated brick and outer sheet of
 - > Solid clinker
 - > Vertically perforated clinker
 - > Face brick

Installation process



Product online



Order description	Length l_d [mm]	Drill hole depth $t_s \leq$ [mm]	Distance a_z [mm]	Curtain wall $h_a \geq$ [mm]	PU [pieces]	Price/100 [EUR]	Article number	EAN
Anchors with A4 stainless steel screws (-E)								
VSD-2G-8Ux145-E	145	155	–	60*	100		8502145600	4061245081939
VSD-2G-8Ux205-E	205	215	20	115	100		8502205600	4039161009771
VSD-2G-8Ux225-E	225	235	40	115	100		8502225600	4039161009788
VSD-2G-8Ux245-E	245	255	60	115	100		8502245600	4039161009795
VSD-2G-8Ux265-E	265	275	80	115	100		8502265600	4039161009801
VSD-2G-8Ux285-E	285	295	100	115	100		8502285600	4039161009818
VSD-2G-8Ux305-E	305	315	120	115	100		8502305600	4039161009825

*Face brick