

## DEKTITE® Soaker Set

**Application range**

- > For waterproofing pipes with large openings

**Properties**

- > Version EDPM (grey)
- > Temperature resistance EPDM (grey)  
permanent 50 °C to +115 °C, short-term up to +150 °C
- > Temperature resistance silikone (red) permanent 50 °C to +200 °C, short-term up to +250 °C

**Included in delivery**

- 1 pipe flashing
- 1 cartridge of EJOPLAST joint sealant
- 1 self-drilling screw set

**Cross references**

Joint sealant  
Tightener  
hose clamp

**Advantages**

- > Large base ensures optimum positioning
- > Reliable and easy installation
- > Seals pipe and roof in a single work step
- > Prevents rainwater back-up

**Notice**

Not usable on smooth surfaces. Profile height max. 45 mm.

**Assembly instruction****Product online**

Order description	For pipe diameter [mm]	Base [mm]	Roof pitch [°]	Content Cartridge [ml]	Content Screws [set]	PU [pieces]	Price/1 [EUR]	Article number	EAN
DF 602 G Set	75–155	410 x 360	0–60	80	30	1		8206024704	4061245013688
DF 603 G Set	114–254	485 x 460	0–60	80	36	1		8206034704	4061245013671
DF 605 G Set	254–406	708 x 635	0–60	310	52	1		8206054704	4061245013664
DF 606 G Set	380–610	1006 x 905	0–60	310	96	1		8206064704	4061245013657

**Order information: All versions also available in red (silicone). Further lengths upon request.**